

AlienFrac™

Super Abrasion Resistant Acid Fracturing Hose A802F

Specification Sheet



Tube: Super abrasion resistant resin and synthetic rubber, full flow **Reinforcement:** 4 to 12 layers of high tensile super flexible spiral steel wire **Middle:** rubbered polyester fabric
Cover: abrasion and weather resistant synthetic rubber **Connectors:** swaged fittings, integral union or flange **Application:** Flexible line using for delivery water-based, oil-based, acid-based and foam fracturing fluids under high pressure in acid, sand and hydraulic fracturing works

胶管型号 Hose Part No.	内径 I.D.	外径 O.D.	工作压力 W.P.	试验压力 P.P.	最小弯曲半径 Min.B.R.	重量 Weight	流量 Volume	接头重量 Connector W.T.	连接形式 Connection Type		
	inch	mm	mm	Psi	Psi	mm	kg/m	bbl/min	m³/min	kg	3" FIG 1502锤击由壬或 3 1/16" 15K API 法兰连接
A802F-28-15K	2	45	95	15000	22500	1400	18	9	1.46	53	
A802F-32-15K		51	103	15000	22500	1400	20	12	1.91	55	
A802F-36-15K	2 1/2	58	121	15000	22500	1500	24	14.8	2.34	57	
A802F-40-15K		64	128	15000	22500	1500	27	18.5	2.90	58	
A802F-44-15K	3	70	135	15000	22500	1600	30	22	3.50	60	
A802F-48-15K		76	141	15000	22500	1600	33	26	4.17	65	
A802F-56-15K	4	89	165	15000	22500	2000	50	35.8	5.70	75	4" FIG 1502锤击由壬或4 1/16" 15K API 法兰连接 4" FIG 1502 hammer union or 4 1/16" 15K API flange
A802F-64-15K		102	171	15000	22500	2000	56	47	7.47	85	
A802F-76-15K	5	120	210	15000	22500	2100	80	62.9	10.00	343	5 1/8" 15K API 法兰连接 5 1/8" 15K API flange
A802F-80-15K		127	215	15000	22500	2100	86	80	11.58	348	
A802F-82-15K		130	220	15000	22500	2100	90	84	12.13	353	
A802F-88-15K	5 1/2	140	240	15000	22500	2200	110	88.6	14.07	560	7 1/16" 15K API 法兰连接 7 1/16" 15K API flange
A802F-96-15K	6	150	250	15000	22500	2300	125	105	16.68	680	
A802F-28-20K	2	44	106	20000	30000	1500	24	9	1.46	60	2" FIG 2002锤击由壬或3 1/16" 20K API 法兰连接 2" FIG 2002 hammer union or 3 1/16" 20K API flange
A802F-32-20K		51	112	20000	30000	1500	26	12	1.91	65	
A802F-36-20K	2 1/2	57	126	20000	30000	1600	32	14.8	2.34	70	2 1/2" FIG 2002锤击由壬或3 1/16" 20K API 法兰连接 2 1/2" FIG 2002 hammer union or 3 1/16" 20K API flange
A802F-40-20K		64	133	20000	30000	1600	36	18.5	2.90	78	
A802F-44-20K	3	69	142	20000	30000	1700	40	22	3.50	85	3" FIG 2002锤击由壬或3 1/16" 20K API 法兰连接 3" FIG 2002 hammer union or 3 1/16" 20K API flange
A802F-48-20K		76	145	20000	30000	1700	42	26	4.17	98	

